

Drywall Cutter LXT®

DCO180Z

18V • 30 000 min⁻¹

Quick and handy drywall cutter

A light cutter for cutting holes and shapes in drywall. Speed of 30 000 min⁻¹. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	30000 min ⁻¹
Collet Capacity	3,18 / 6,35 mm
Sound Power Level (L _{WA})	88 dB(A)
Sound Pressure Level (L _{pA})	80 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Rotation Without Load	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Rotation Without Load	1,5 m/s ²
Product net weight	1,2 kg
Tool weight with battery	1,5 - 1,8 kg
Product Dimensions (L x W x H):	313 x 77 x 118 mm
Vacuum cleaner connection Ø in / out	25 / 31 mm

User benefits

- Slim body design for a good grip
- Electronic overload protection protects the user and the device
- Anti-restart function minimises accidental start-up
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381674522

Link to product - www.makita.com



Related products

Standard AC

733240-2 (2x)

Drywall Bit



Optional AC

191669-8

Drywall guide bit 3,18 mm



193446-8

Drywall Guide Bit 3,18 mm



193449-2

Dust nozzle Ø 25 / 31 mm



733240-2 (2x)

Drywall Bit



763606-2

Collet Nut



763608-8

Collet cone 6,35 mm, (1/4")



763677-9

Collet Cone 1/8"



193447-6

Drywall Guide Bit 6,35 mm



838062-6

Makpac Type 1 Inner tray



Other

[User manual](#)

[Parts drawing](#)