

Auto Feed Screwdriver LXT® DFR550Z

18V • 25 – 55 mm • 4 000 min⁻¹

Quick screwdriving with auto-feed system

A cordless 18V LXT® screwdriver for screw strips with a speed of 4 000 min⁻¹ and a robust aluminium auto-feed system for 25 – 55 mm screws. A precise depth control switch and screw guide ensure accuracy and prevent slanted screw feeds. Tool only, battery and charger not included.



Technical specifications

Voltage LXT	✓
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	4000 min ⁻¹
Screwdriver Bit Length	157 mm
Driving Shank	1/4 "
Capacity Drywall Screw	4,0 mm
Collated drywall screw	25 - 55 mm
Sound Pressure Level (L _{pA})	78 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Screwdriving Without Impact	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor), Screwdriving Without Impact	1,5 m/s ²
Tool weight with battery	2,1 - 3,1 kg
Product Dimensions (L x W x H):	424 x 80 x 238 mm

User benefits

- Dust protected construction.
- Electronic overload protection protects the user and the device
- Depth adjustment
- Ergonomic soft grip handle provides increased comfort
- Compact and lightweight design
- Conveniently located forward/reverse switch
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381669467

Link to product - www.makita.com



Related products

Optional AC

194500-1

Extension handle 890 – 990 mm



281217-6

Carrying Hook



837631-0

MakPac (3) Inlay



P-67795

Screw Bit, PH2, 157 mm, Ø 5 mm, 3



Other

[User manual](#)

[Parts drawing](#)