Rotary Hammer LXT®

DHR202Z

18V • SDS-Plus • 20 mm • 2.0 J

Professional three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1 100 min-1. Impact energy of 2.0 J and max. drilling capacity of 20 mm in concrete. Tool only, battery and charger not included.

LXT

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Max Output Power	330 W
No load speed	0 - 1100 min^{-1}
Impacts per Minute (IPM)	0 - 4000 min^{-1}
Max. Drilling Diameter in Wood	26 mm
Max. Drilling Diameter in Masonry	20 mm
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 10 mm
Impact Energy	1,9 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓

User benefits

- Battery protection system automatically shuts off power when the battery level is low
- LED light illuminates the work site
- Impact drilling, non-impact drilling and spike function
- Reversing switch
- Compact and ergonomic design
- Works with 18V Li-ion battery (not 1.3Ah battery)
- Easy blade setting system for fast blade installation

EAN 0088381658119

Link to product - www.makitauk.com

Related products

Standard AC

324219-0
Depth Gauge

—

Optional AC

193472-7
Dust extraction set Ø 25 / 31 mm

821551-8
Makpac case (3)

837634-4
MakPac (3) Inlay

D-16368
Chisel set SDS-PLUS, 5 pcs

D-74136
Drill Bit Set T.C.T, SDS-PLUS, 4 pcs

Other

User manual

Parts drawing