

# Rotary Hammer LXT®

## DHR241Z

18V • SDS-Plus • 20 mm • 2.0 J

Professional long-framed, three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 1 100 min<sup>-1</sup>. Impact energy of 2.0 J and max. drilling capacity of 20 mm in concrete. Tool only, battery and charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 min <sup>-1</sup>
Impacts per Minute (IPM)	0 - 4000 min <sup>-1</sup>
Max. Drilling Diameter in Wood	26 mm
Max. Drilling Diameter in Concrete	20 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 12 mm
Impact Energy	1,9 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L <sub>WA</sub> )	97 dB(A)

### User benefits

- 3-Mode operation for "Rotation Only", "Hammering with Rotation" or "Hammering Only" for multiple applications
- One touch sliding chuck enables quick and easy bit changes
- Reversing switch
- Ergonomic chassis design ensures a good working position.
- Battery protection circuit protects against overloading, over-discharging and over-heating

**EAN 0088381661768**

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ Standard AC

324219-0  
Depth Gauge

---

## ■ Optional AC

821551-8  
Makpac case (3)



837641-7  
MakPac (3) Inlay



D-16368  
Chisel set SDS-PLUS, 5 pcs

---



## ■ Other

User manual

Parts drawing