

# Rotary Hammer LXT®

## DHR242Z

18V • SDS-Plus • 24 mm • 2.0 J

Professional brushless, three-mode rotary hammer

An efficient rotary hammer for SDS-Plus bits with an anti-vibration handle. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min<sup>-1</sup>. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete. Tool only, battery and charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 950 min <sup>-1</sup>
Impacts per Minute (IPM)	0 - 4700 min <sup>-1</sup>
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	4 - 16 mm
Impact Energy	2,0 J
Drilling diameter with TCT core bit	54 mm
Adapted for SDS-PLUS bits	✓
Electronic brake	✓
Sound Power Level (L <sub>WA</sub> )	101 dB(A)

### User benefits

- Brushless maintenance-free and long-life motor
- Low power consumption thanks to brushless motor
- Battery protection circuit protects against overloading, over-discharging and over-heating

**EAN 0088381654326**

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## Standard AC

324219-0  
Depth Gauge

---

## Optional AC

196165-5  
HEPA filter



199557-7  
Replacement Hepa filter



199977-5  
Hepa Filter



324219-0  
Depth Gauge



424474-5  
Sealing Cap



821552-6  
Makpac case (4)



835A31-4  
MakPac Type 4 Inlay



D-16368  
Chisel set SDS-PLUS, 5 pcs



## Other

[User manual](#)

[Parts drawing](#)