

Slide Compound Mitre Saw LXT®

DLS713NZ



Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
No load speed	2200 min ⁻¹
Capacity 90°	52 x 300 mm
Capacity 45°	52 x 212 mm
Capacity 45° left	25 x 300 mm
Max. Bevel Range (Left)	45 / 5 °
Max. Mitre Range (Left)	47 / 57 °
Blade Diameter	190 mm
Bore Size (Arbor Diameter)	20 mm
Sound Power Level (L _{WA})	98 dB(A)
Sound Pressure Level (L _{pA})	88 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery	12,4 - 12,7 kg

EAN 0088381876995

Link to product - www.makita.com

User benefits

- The double slide mechanism takes up little space and ensures vibration-free precise cutting
- Lightweight for reduced operator fatigue
- Electric brake for maximum productivity and increased operator safety
- Battery protection system automatically shuts off power when the battery level is low



Related products

Standard AC

122852-0
Dust bag



726018-0
Carbide Tipped Saw Blade 190

Optional AC

122472-0
Repetitive Cut Stop



122571-8
Vertical Vice Assembly



122852-0
Dust bag



123101-8 (2x)
Side Holder



762001-3
Triangular Rule



783203-8
Hex Wrench 5 Mm



A-86147
Saw Blade T.C.T 190 mm



B-64191
Circular Saw Blade, Efficut, TCT,



B-68638
Circular Saw Blade, Efficut, TCT,



Other

User manual

Parts drawing