

Circular Saw LXT®

DSS611Z

18 V • 3 700 min⁻¹ • 165 mm



LXT

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	3700 min ⁻¹
Max. Cutting Depth at 90°	57 mm
Max. Cutting Depth at 45°	40 mm
Max. Cutting Depth at 50°	36 mm
Max. Bevel Range (Left)	0 - 50 °
Blade Diameter	165 mm
Bore Size (Arbor Diameter)	20 / 30 mm
Sound Power Level (L _{WA})	104 dB(A)
Sound Pressure Level (L _{pA})	96 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Cutting Wood	≤ 2,5 m/s ²
Vibration Uncertainty (K Factor),	1,5 m/s ²

EAN 0088381663014

Link to product - www.makitauk.com

User benefits

- Smooth cutting at high rotational speed of 3,700 RPM
- Ergonomic soft grip handle provides increased comfort
- Safety cover with calibration line for adjusting cutting depth
- Bevel cuts 0° - 45°
- Large bevel lock lever; Easy to operate even if the machine is placed close to the wall, because you do not need to reach for the rear of the machine to turn the lever
- Externally accessible brushes for easy serviceability



Related products

■ Standard AC

164095-8
Parallel Guide



783203-8
Hex Wrench 5 Mm



■ Other

User manual

Parts drawing