

## Impact Driver LXT®

# DTD154Z

18V • 1/4" • 175 Nm • 0 – 3 600 min<sup>-1</sup>

**Extra-compact brushless impact driver with three power settings for quick driving**

A compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 175 Nm. Three power settings, suitable for quick driving. Handy LED light. Tool only, battery and charger not included.



### Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 / 2100 / 3600 min <sup>-1</sup>
Max Fastening Torque Impact Drill	175 Nm
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1100 / 2600 / 3800 min <sup>-1</sup>
Driving Shank	1/4 "
Sound Power Level (L <sub>WA</sub> )	107 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	96 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

**EAN 0088381824125**

Link to product - [www.makitauk.com](http://www.makitauk.com)

### User benefits

- Low power consumption thanks to brushless motor
- Compact and lightweight design
- The screw tip is securely held in place by a quick lateral stroke
- LED light illuminates the work site
- eXtreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Quick mount for 1/4 "screwdriver
- Battery protection system automatically shuts off power when the battery level is low



# Related products

## Standard AC

346317-0  
Belt Hook



## Optional AC

194250-8  
Adaptor Chuck - 1/4 Hex Keyless



821550-0  
Makpac case (2)



837670-0  
MakPac (2) Inlay



B-42961  
Threaded Rod Socket M6



B-42977  
Threaded Rod Socket M8



B-42983  
Threaded Rod Socket M10



## Other

[User manual](#)

[Parts drawing](#)