

Reciprocating Saw CXT®

JR105DZ

12V max • 0 – 3 300 min⁻¹ • 13 mm

Compact reciprocating saw for light use, also accepts jigsaw bits

A straight-framed light and small reciprocating saw offers access to tight places. Two separate switches enable diverse working postures. Stroke length of 13 mm, stroke rate can be adjusted between 0 – 3 300 min⁻¹ from a switch. LED light. Tool only, battery and charger not included.



■ Technical specifications

CXT Battery	✓
Nominal Battery Voltage	12 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	0 - 3300 min ⁻¹
Length of Stroke	13 mm
Max. Cutting Capacity in Wood (90°)	50 mm
Max. Cutting Capacity in Steel Pipe	50 mm
Sound Power Level (L _{WA})	89 dB(A)
Sound Pressure Level (L _{pA})	81 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level, Cutting Boards	8,0 m/s ²
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s ²
Vibration Level, Cutting Wooden Beam	8,0 m/s ²
Vibration Uncertainty (K Factor), Cutting Wooden Beam	1,5 m/s ²

■ **EAN 0088381800907**

Link to product - www.makita.com

■ User benefits

- LED light illuminates the work site
- The rubber coating on the handle ensures a firm working grip
- Battery protection system automatically shuts off power when the battery level is low



Related products

■ Standard AC

195776-3
Accessory Set

783201-2
Hex Wrench 3Mm



■ Optional AC

821549-5
Makpac case (1)



838313-7
Makpac Type 1 Inner tray



■ Other

[User manual](#)

[Parts drawing](#)