

## Combi Drill LXT®

### DHP487Z

18V • 40 Nm • 0 – 1 700 min<sup>-1</sup>

**A powerful, brushless general-use impact drill for screwdriving and drilling**

An efficient, brushless drill for screwdriving and drilling with or without hammer action, two power settings. Max. torque of 40 / 23 Nm. A versatile tool for fitters, builders and maintenance staff. Integrated LED light. Tool only, battery and charger not included



#### Technical specifications

|  |                                    |
|--|------------------------------------|
| Voltage LXT                            | ✓                                  |
| Nominal Battery Voltage                | 18 V                               |
| No load speed                          | 0 - 500 / 1700 min <sup>-1</sup>   |
| Max. fastening torque Hard/Soft        | 40 / 25 Nm                         |
| Torque setting                         | 20                                 |
| Impacts per Minute (IPM)               | 0 - 7500 / 25500 min <sup>-1</sup> |
| Max. Drilling Diameter in Wood         | 36 mm                              |
| Drilling Capacity Wood (Auger Bit)     | 36 mm                              |
| Drilling Capacity Wood (Self-feed bit) | 35 mm                              |
| Max. Drilling Diameter in Masonry      | 13 mm                              |
| Max. Drilling Diameter in Concrete     | 13 mm                              |
| Max. Drilling Diameter in Steel        | 13 mm                              |
| Driving Shank                          | 1/2"-20UNF "                       |
| Drill Chuck Capacity                   | 1,5 - 13 mm                        |
| Electronic brake                       | ✓                                  |
| Sound Power Level (L <sub>WA</sub> )   | 94 dB(A)                           |

#### User benefits

- Optimum handle design
- LED light illuminates the work site
- Highly efficient and compact machine for professional use
- Battery protection system automatically shuts off power when the battery level is low
- Electronic overload protection protects the user and the device

**EAN 0088381740333**

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## Standard AC

**251314-2**

Truss Head Screw M4\*12, Td140D



**346317-0**

Belt Hook



**784637-8**

Screw Bit, Ph2 – S6, 45 Mm, Double



## Optional AC

**251314-2**

Truss Head Screw M4\*12, Td140D



**346317-0**

Belt Hook



**346449-3**

Belt Hook



**450128-8**

Battery cover, LXT®, 14,4 – 18V



**763252-1**

Keyless Drill Chuck



**784637-8**

Screw Bit, Ph2 – S6, 45 Mm, Double



**B-49432**

Drill Bit Set, TCT, M-Force, 18 pcs



**D-72849**

Metal drill bit set HSS-TiN, 10 pcs



**D-72861**

Wood drill bit set, 5 pcs



**D-72877**

Drill bit set T.C.T, 5 pcs



## Other

[User manual](#)

[Parts drawing](#)