

Rotary Hammer LXT®

DHR243Z

18V • SDS-Plus • 24 mm • 2.0 J

Brushless, three-mode rotary hammer with quick-change chuck

An efficient rotary hammer with an anti-vibration handle and quick-change chuck that accepts SDS-Plus bits. Suitable for impact and unstressed drilling, plus chipping. Speed range of 0 – 950 min⁻¹. Impact energy of 2.0 J and max. drilling capacity of 24 mm in concrete. Tool only, battery and charger not included.



Technical specifications

Vibration Level, Hammer Drilling Into Concrete	15,8 m/s ²
Vibration Uncertainty (K Factor), Hammer Drilling Into Concrete	1,5 m/s ²
Vibration Uncertainty (K Factor), Chiselling	1,5 m/s ²
Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 950 min ⁻¹
Impacts per Minute (IPM)	0 - 4700 min ⁻¹
Max. Drilling Diameter in Wood	27 mm
Max. Drilling Diameter in Concrete	24 mm
Max. Drilling Diameter in Steel	13 mm
Optimum Drilling Diameter Range in Concrete	6 - 12 mm
Impact Energy	2,0 J

User benefits

- Brushless maintenance-free and long-life motor
- Impact drilling, non-impact drilling and spike function
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381654722

Link to product - www.makitauk.com



Related products

Standard AC

194079-2 Quick Change Drill Chuck 13 mm,		324219-0 Depth Gauge	
--	---	--------------------------------	---

Optional AC

195180-6 Dust Collecting Cap		196165-5 HEPA filter	
196173-6 Exchangeable chuck set		199977-5 Hepa Filter	
324219-0 Depth Gauge		424474-5 Sealing Cap	
821552-6 Makpac case (4)		835A31-4 MakPac Type 4 Inlay	
837649-1 MakPac (4) Inlay		D-16368 Chisel set SDS-PLUS, 5 pcs	

Other

User manual

Parts drawing