

Reciprocating Saw LXT®

DJR187Z

18V • 0 – 3 000 min⁻¹ • 32 mm

Efficient brushless reciprocating saw

An efficient brushless reciprocating saw for spark-free cutting of metal and demolition work for professional use. Two speed settings, stroke length of 32 mm and stroke rate of 0 – 2 800 min⁻¹ with continuous control from the switch. Quick-release blade attachment. Tool only, battery and charger not included.



Technical specifications

Vibration Level, Cutting Boards	16,5 m/s ²
Vibration Level, Cutting Wooden Beam	15,5 m/s ²
Vibration Uncertainty (K Factor), Cutting Boards	1,5 m/s ²
Vibration Uncertainty (K Factor), Cutting Wooden Beam	1,5 m/s ²
Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Strokes per Minute (SPM)	0 - 2300 / 3000 min ⁻¹
Length of Stroke	32 mm
Max. Cutting Capacity in Wood (90°)	255 mm
Max. Cutting Capacity in Steel Pipe	130 mm
Sound Power Level (L _{WA})	95 dB(A)
Sound Pressure Level (L _{pA})	84 dB(A)
Noise Uncertainty (K Factor)	3 dB(A)

User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381806121

Link to product - www.makitauk.com



Related products

Optional AC

821620-5 Plastic Carrying Case		B-05169 Reciprosaw Blade 152 x 0,9 mm	
B-49834 Reciprosaw Blade 152 x 1.25 mm		B-49840 Reciprosaw Blade 228 x 1.25 mm	
B-49856 Reciprosaw Blade 305 x 1.25 mm		B-55566 Reciprosaw Blade 100 x 1,25 mm	
B-55572 Reciprosaw Blade 152 x 1,25 mm		B-55572-10 Reciprosaw Blade 152 x 1,25 mm	
B-55588 Reciprosaw Blade 228 x 1,25 mm		B-55588-10 Reciprosaw Blade 228 x 1,25 mm	
B-55594 Reciprosaw Blade 305 x 1,25 mm		B-55594-10 Reciprosaw Blade 305 x 1,25 mm	

Other

User manual

Parts drawing