

Impact Driver LXT®

DTD154Z

18V • 1/4" • 175 Nm • 0 – 3 600 min⁻¹

Extra-compact brushless impact driver with three power settings for quick driving

A compact and light brushless impact driver with a hex. 1/4" drive shank. A small and light tool that is easy to use but offers a max. fastening torque of 175 Nm. Three power settings, suitable for quick driving. Handy LED light. Tool only, battery and charger not included.



Technical specifications

Vibration Level, Impact Tightening of Fasteners of the Maximum Capacity of the Tool	12,5 m/s ²
Vibration Uncertainty (K Factor), Impact Tightening of Fasteners of the Maximum Capacity of the Tool	1,5 m/s ²
Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 / 2100 / 3600 min ⁻¹
Max Fastening Torque Impact Drill	175 Nm
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1100 / 2600 / 3800 min ⁻¹

User benefits

- LED light illuminates the work site
- Battery protection system automatically shuts off power when the battery level is low

EAN 0088381824125

Link to product - www.makita.uk.com



Related products

Standard AC

346317-0

Belt Hook



Optional AC

194250-8

Adaptor Chuck - 1/4 Hex Keyless



821550-0

Makpac case (2)



837670-0

MakPac (2) Inlay



B-42961

Threaded Rod Socket M6



B-42977

Threaded Rod Socket M8



B-42983

Threaded Rod Socket M10



Other

User manual

Parts drawing