

Chainsaw LXT® DUC355Z

18V X2 • 20 m/s • 35 cm / 14"

Efficient brushless saw with a high chain speed for heavyduty use

A versatile and efficient brushless saw with a chain speed of 20 m/s, designed for use at construction sites, at home or at the summer cottage, or for cutting thin tree stems. A high 36V is achieved with two 18V LXT® batteries. Equipped with a 14" guide bar and tool-less chain and bar tensioning. Tool only, battery and charger not included.





Technical specifications

Vibration Uncertainty (K Factor), Cutting Wood Voltage LXT Nominal Battery Voltage Battery Chemistry (Ni-Cd / Ni-MH / Li- ion)	1,5 m/s² √ 2 x 18 V Li-ion
Max Output Power Chain Oil Tank Max. Chain Speed (No Load) Chain Speed at Max. Power chain bar length Chain Pitch Chain Gauge Chain Gauge Number of Drive Links Sound Power Level (L _{WA})	1100 W 0,2 L 20 m/s 20,0 m/s 350 mm (14") 3/8 " 0,043 " 1,1 mm 52 98,7 dB(A)
Sound Pressure Level (L_{pA})	87,7 dB(A)

User benefits

- Classic bolts instead of tool-less straps of chain and sword
- Constant speed control maintains constant speed under load
- Extreme Protection Technology (XPT) is engineered for improved dust and water resistance for operation in harsh conditions
- Cordless for instant start-up, zero emissions and reduced maintenance
- Battery protection system automatically shuts off power when the battery level is low



EAN 0088381870641

Link to product - www.makitauk.com

Related products

Standard AC

165246-6 Guide bar, 14" / 35 cm, 3/8", 1,1 mm

419288-5 Chain Protection Cover 14" / 35 cm

782027-9 Box Wrench Oil vessel set 713099-3

199897-3

182229-1

199897-3

D-70948

Tookite

1

Oil vessel set

Round File & Guide Set, Ø 4,0 mm

Chain Oil 100 ml

Saw Chain 14

Optional AC

165246-6 Guide bar, 14" / 35 cm, 3/8", 1,1 mm

196741-5 Saw Chain, -52, 3/8", 1.1 mm, 14" /

419288-5 Chain Protection Cover 14" / 35 cm

D-72154 Sharpening Set 4,0 mm Ø

Other

User manual

Parts drawing

@===